

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/518787

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number  
**WO 2004/000391 A1**

(51) International Patent Classification<sup>7</sup>: **A61M 1/36**,  
B01D 19/00, B01F 5/00

(21) International Application Number:  
PCT/IB2003/002281

(22) International Filing Date: 26 May 2003 (26.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
MI2002A001390 24 June 2002 (24.06.2002) IT  
MI2002A001389 24 June 2002 (24.06.2002) IT

(71) Applicants (for all designated States except US): **GAMBRO LUNDIA AB** [SE/SE]; no. 16, Magistratsvagen, S-22643 Lund (SE). **SEMENZATO, Nicolas** [FR/FR]; no. 7, rue Maryse Bastié, F-69330 Meyzieu (FR).


(72) Inventors; and  
(75) Inventors/Applicants (for US only): **CHEVALLET, Jacques** [FR/FR]; no. 8, route de Ternay, F-69360 Serezin du Rhone (FR). **RIBOLZI, Francesco** [IT/IT]; no. 1, via Camatta, I-41100 Modena (IT). **FRUGIER, Alain** [FR/FR]; no. 89, rue du Grand Paradis, F-38230 Tignieu (FR).

(74) Agent: **VILLANOVA, Massimo**; Gambro Intellectual Property Department, c/o Gambro Dasco S.p.A., no. 66, via Modenese, I-41036 Medolla (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE (utility model), DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: **GAS SEPARATION DEVICES**



(57) Abstract: A description is given of a gas separation device for a physiological fluid, comprising a containing body (6) having at least a first inlet aperture (7) for a physiological fluid, positioned with a tangential direction of access, at least one outlet aperture (9) for the said fluid, spaced apart from the said inlet aperture, and a guide element (17) housed within the said body. The guide element (17) has a continuous active surface (15) designed to contact and guide the said fluid and delimits, together with the containing body (6), a first annular chamber (20) into which the first inlet aperture (7) opens directly.

WO 2004/000391 A1